

Technical specifications



MODEL

- Interior
- Construction
- Detergent pump
- Rinse additive dispenser
- Basket
- Working height
- Cycle duration (without rinsing)
- Water/cycle consumpt.
- Boiler capacity
- Boiler heating element
- Tank heating element
- Wash pump
- Drain pump
- Total power
- Electrical connections
- Outlet hose connection
- Inlet hose connection

| | AP 43 E | AP 48 E | AP 53 E | AP 60 E |
|----------------------------------|----------------------|----------------------|----------------------|----------------------|
| Interior | Self-cleaning | Self-cleaning | Self-cleaning | Self-cleaning |
| Construction | Double skin | Double skin | Double skin | Double skin |
| Detergent pump | standard | standard | standard | standard |
| Rinse additive dispenser | standard | standard | standard | standard |
| Basket | 350 x 350 - Ø 360 mm | 400 x 400 - Ø 400 mm | 450 x 450 mm | 500 x 500 mm |
| Working height | 280 mm | 280 mm | 270 mm | 330 mm |
| Cycle duration (without rinsing) | 152/182/242/484 sec. | 152/182/242/484 sec. | 152/182/242/484 sec. | 152/182/242/484 sec. |
| Water/cycle consumpt. | 3,5 - 4 l | 3,5 - 4 l | 4 - 5 l | 5 - 6 l |
| Boiler capacity | 6 l | 6 l | 7,5 l | 7,5 l |
| Boiler heating element | 5000 W | 5000 W | 6000 W | 6000 W |
| Tank heating element | 225 W | 225 W | 500 W | 500 W |
| Wash pump | 400 W | 400 W | 500 W | 500 W |
| Drain pump | 100 W | 100 W | 100 W | 100 W |
| Total power | 5400 W | 5400 W | 6500 W | 6500 W |
| Electrical connections | 400V 3 N 50 Hz | 400V 3 N 50 Hz | 400V 3 N 50 Hz | 400V 3 N 50 Hz |
| Outlet hose connection | Ø 28 mm | Ø 28 mm | Ø 31 mm | Ø 31 mm |
| Inlet hose connection | 3/4" G (2-4 Bar) | 3/4" G (2-4 Bar) | 3/4" G (2-4 Bar) | 3/4" G (2-4 Bar) |

The manufacturer reserves the right to update technical specifications without notice. • Some of the features shown may not be available as standard.

Required hardness of the water supplied between 4° and 10° f (French hardness degrees) .

In case of higher levels of hardness, a water softner must be used.

A **CE** product – complies with European standards.



Base stand 43|48 | 53|60



Closed base stand |60

A revolution in hygiene | AP fresh water glasswasher

AP

43 E | 48 E | 53 E | 60 E

43 E



48 E



53 E



60 E



HOONVED

HOONVED S.r.l.



Col. 35100 ed. 01/08



AP|43 E

AP marks a revolution in glasswashing: outstanding wash results without compromise. The AP series of professional glasswashers complies with the high quality standards Hoonved is worldwide famous for. With its Sunrise series Hoonved was the first who introduced on the market the concept of glasswashing with fresh water at all stages of washing and rinsing more than 20 years ago.

43 E



AP is unrivalled by other professional glasswashing systems.

The water pressure is five times stronger than in the conventional water recycle glasswashers.

The Steaker Heating Element placed under the tank:

- allows the heating of the washing water
- optimizes the heating performances
- avoids backdirt



AP|48 E

New design with a double panel housing in stainless steel AISI 304 and a moulded handle.

The hermetic seal door assures the perfect thermo-acoustic isolation of the machine.

The rotating upper and lower wash/rinse systems in stainless steel are adjustable.



48 E

AP is the first glasswasher with an untimed "volumetric" final rinse.

If the main water pressure drops, the AP increases the duration of the rinse cycle ensuring maximum hygiene at the end of the cycle.



AP|53 E

Digital touch panel control with 4 washing cycles. Wash and rinse temperatures are displayed on the touch panel. Self diagnosis of machine functioning through alarms. Adjustable times and washing temperatures on each cycle.



The only absolute guarantee of cleanness

Fresh water for every cycle

Impeccable results

Guaranteed temperature

of the water during the rinse cycle

Optimized consumption levels

Silent operation

Double paneling

Self-cleaning Interior

Easy maintenance

High pressure

Induction heating

technology

Volumetric rinse cycle for maximum performance

Stops immediately when insufficient water pressure



AP|60 E

AP machines rationalize the use of detergent and rinse aid dosing automatically the required quantity. Rinse aid pump and detergent pump are standard features on all the models.

60 E

